



5G Single-Use Location and Condition Tracker



LOCATION

Hyper-accurate location data.



CLIMATE MONITORING

Insight into a shipment's environment.



SHIPMENT INTEGRITY

Shock sensors indicate shipment damage.



ASTOUNDING BATTERY LIFE

Exceeds any shipment length requirement.

Tive Solo 5G Single-Use Tracker

The Tive Solo 5G™ is a single or multi-use multi-sensor tracker that measures hyper-accurate location, temperature, humidity, shock, and light exposure of shipments. Using the latest global cellular, WiFi, and GPS technology and on-board sensors, the Solo 5G reports real-time sensor data to the Tive SaaS Platform. From there, logistics professionals actively manage shipments and eliminate preventable shipment delays and damage. A single button activates the tracker, and there's no need to return it, eliminating complex reverse logistics operations.



Committed to Sustainability

The Tive Solo 5G can be recycled with Tive's Green Program



Designed for these shipments



Cold Chain



High-Value



Industrial



Automotive



Time Sensitive

Specifications

Tive Solo Single-Use Tracker



Actual Size

CASE SPECIFICATIONS

Case Material:
UL 94-V0 flame retardant plastic

Dimensions:
96 mm x 58 mm x 19.5 mm

Weight:
3.5 ounces (100 grams)

Mounting:
3M Adhesive, Cable Tie

IP Rating:
IP67

SENSORS

Condition Sensors:
Temperature, Humidity, Light,
Motion, Shock, With configurable
thresholds for alerts

Temperature Accuracy:
 $\pm 0.5^{\circ}\text{C}$, NIST Traceable
ISO 17025 calibration certificate
(3-points) available
 -20°C to 60°C

CERTIFICATIONS

FCC, CE, RoHS, UN38.3

GLOBAL CELLULAR CONNECTIVITY

Transmission Type:
LTE-M with GSM fallback

Cellular Coverage:
Global bands: B1/B2/B3/B4/B5/B8/
B12/B13/B18/B19/B20/B25/B28

MEMORY STORAGE

Up to 25,000 records

POWER SOURCE

Rechargeable Lithium-Ion battery
(3.7V, 2600 mAh / 9.62Wh capacity)
Charging Method: USB Micro

Battery Life:
Over 90 days (60 mins reporting interval)
Shelf life of 180 days

LOCATION

Location Method:
Cellular, GPS, Wi-Fi Geolocation

Location Accuracy:
< 500 m

WIRELESS SENSOR SUPPORT

Tive Temperature Beacon (TT-6000)

FOR FURTHER INQUIRIES ABOUT THE TIVE SOLO, PLEASE CONTACT [SALES@TIVE.COM](mailto:sales@tive.com)

Condition Sensors



Temperature



Light



Humidity



Shock



Motion